

Declared Performance of the Product

Snow Fence

- 1 Designation and trade name of the construction product:
Product kit for the installation of a snow fence in accordance with the system: Snow fence
- 2 The construction product's type designation/names per constituent component:
- Rail tube 1.0 m / 2.4 m
 - Angle tube 0-90°/ 90°
 - Profiled sheet metal snow fence 1.255 m / 2.345 m
 - Bracket concrete tiles / clay tiles
 - Anchor plate, load-bearing roof underlay
 - Batten bracket, simplified roof underlay
 - Bracket, profiled sheet metal / flat roof long
 - Bracket smooth roof
 - Fold mount / fold mount, pre-fabricated panel roof
 - Mounting plate 375 x 375 mm / Mounting plate shingle
 - Riser, smooth roof
 - Mounting plate façade ladder (Hygge type)
 - Biber tile mount
 - Biber tile bracket
- 3 Intended Uses for the Construction Product
- Snow fence
 - Attachment of personal fall protection equipment
 - Installation on intended roof types in accordance with the specification on page 2
- 4 Manufacturer's Name and Contact Address:
CW Lundberg Industri AB
Landsvägen 52, Box 138, 792 22 Mora, Sweden
- 5 Authorised representative, if such has been appointed: **Not applicable**
- 6 Assessment and inspection of performance:
Assessment and continual inspection performed by supervisory body, and in-house inspections.
- 7 Technical specifications:
Supervisory body, Research Institutes of Sweden (RISE)
Certificate 12 71 01
Applied technical specification: SS 831335 and ÖNORM B 3418:2012

- 8 Construction product's performance:

Essential properties	Performance	Remarks
Load capacity (according to A.2)	3.3 kN	Austrian Standard (ÖNORM) B 3418:2012 **
Load capacity (according to A.3)	3.5 kN	
Load capacity (according to A.4)	3.9 kN	
Mechanical strength (according to Section 6)		SS 831335
- Static load	5 kN/m*	
- Dynamic load	≥ 100 kg	
Corrosion resistance	Satisfies	

- 9 Performance of the product for the aforementioned product is consistent with the Performance of the product specified in Section 8. This document is issued at the responsibility of the manufacturer in accordance with Section 4.

5 kN/m* indicates load capacity at a c-c distance of 1.2 m between mounts.

Signed on behalf of the manufacturer by:



Thomas Lundberg
Managing Director

Mora, 24 October 2022



The Performance of the product indicated below does not constitute a portion of the declared Performance of the product. The manufacture issues additional information about the product which affects or which may affect its use.

Installation of the snow fence is done in accordance with Installation Instruction M-204, on PVC, ECB/FPO-based membranes in accordance with M-085 and M-349, on bitumen-based membranes in accordance with M-350, on shingled roofs in accordance with M-132, on weldable EPDM membranes in accordance with M-351 or M-352 and on sheet metal roofs in accordance with M-222, Hygge sheet metal roofs in accordance with M-301, on tiled roofs in accordance with M-223 and on Biberschwanzziegel roof tile in accordance with M-332 (snowfence according to M-338).

Optional extra, flag with snow-depth indicator.

Products can be selected in various colours of powder lacquer for design.

Other Performance

<i>Properties</i>	<i>Performance</i>	<i>Technical specifications</i>
Corrosion resistance (corrosivity class C4)	40 years	EN ISO 12944-2
Exterior reaction to fire (according to 7.3)	B _{roof}	EN 516:2006

Requirements on PVC, ECB/FPO-based membranes

The waterproofing membrane must satisfy the requirements set out in EN 13956, as well as the following requirements:

<i>Properties</i>	<i>Requirement</i>	<i>Technical specifications</i>
Tensile strength	min. 500 N/50 mm	EN 12311-2
Tear resistance	min. 110 N	EN 12310-2
Shear resistance at extensions	min. 450 N/50 mm	EN 12317-2
Peel strength at extensions	min. 150 N/50 mm	EN 12316-2

Requirements for bitumen-based membranes

The waterproofing membrane must satisfy the requirements set out in EN 13707:2004+A2:2009, as well as the following requirements:

<i>Properties</i>	<i>Requirement</i>	<i>Technical specifications</i>
Tensile strength in longitudinal and transverse directions	min. 300 N/50 mm	EN 12311-1
Tear resistance	min. 150 N	EN 12310-1
Shear resistance at extension and longitudinal and transverse directions	min. 500 N/50 mm	EN 12317-1
Peel strength	min. 125 N/50 mm	EN 12316-1

Requirements for weldable EPDM membranes

The waterproofing membrane must satisfy the requirements set out in EN 13956, as well as the following requirements:

<i>Properties</i>	<i>Requirement</i>	<i>Technical specifications</i>
Tensile strength	min. 400 N/50 mm	EN 12311-2
Tear resistance	min. 12 N	EN 12310-2
Shear resistance at extensions	min. 200 N/50 mm	EN 12317-2
Peel strength at extensions	min. 80 N/50 mm	EN 12316-2

Choice of attachment in concrete

Installation may only be done with a concrete mount M10 (concrete expander, safety expander or chemical anchor) in at least class A2 that withstands a traction load of at least 10 kN a tensile load of at least 10 kN.

In order to be able to install the anchor loop directly onto concrete, a suitable anchor must be chosen by calculating the load for the class in question on the underlying surface; moreover, one must take into account the type of reinforcement, the distance from the edge and other mounts, the thickness of the concrete and other conditions that may affect the safety of the mount. On the basis of the calculations made

and the installation conditions in question, the type and dimension of the anchor is determined, as are the detailed installation instructions that shall be consistent with the manufacturer's instructions.